



Do not scale from this drawing.

EDINBURGH

THE CITY OF EDINBURGH COUNCIL

SFN

Sacyr - Farrans - Neopol

Key

Existing Trees/vegetation to be retained

Existing Trees/vegetation to be removed

Existing / Proposed walls

Pre-cast concrete flags 450x600x63mm, laid in a staggered bond at 90° to the kerb with 5-10mm joints. Laid in accordance with BS 7533-4*

Caltness natural stone paving flags (castle blend), 450xrandom lengthx65mm, laid in a staggered bond with 5-10mm joints. Laid in accordance with BS 7533-4, as supplied by BBS (or similar approved)*

Scoutmoor sandstone natural stone paving (diamond sawn finish), 450x450x63mm, laid in a staggered bond with 5-10mm joints. Laid in accordance with BS 7533-4 as supplied by BBS (or similar approved)*

*For vehicle crossover locations and details / paving buildups please refer to Engineer's roadworks package and construction detail drawings.

Asphalt footpath, to engineers detail

Pedestrian deterrent paving: Estanh Grey Granite setts, flamed finish, 200x100mm with deep recessed joints. As supplied by BBS (or similar approved).

Separator strip: width <0.5m Estanh Grey Granite setts, flamed finish 200x100mm with deep recessed joints, width >0.5m paving to match adjacent areas

Cycle route, to engineers detail

Grasscrete: Grassgrid product as supplied by Aggregate Industries (or similar approved), 366x274x100mm

Tactile paving

Ladder tactile paving

Specimen trees: refer to planting schedule and outline specification on sheet 1 for further details

Tree grille (to semi mature trees in hard landscape): Castle grille 1800x1800mm infilled with paving to match surroundings, as supplied by GreenBlue Urban (or similar approved) Orientation of grille to match surrounding paving direction

Linear root barrier: installed for trees in soft adjacent to pavements or utilities, ReRoot1000 as supplied by GreenBlue Urban (or similar approved)

Gross seeding: refer to outline specification on sheet 1

Ornamental shrub / herbaceous planting: refer to planting schedule and outline specification on sheet 1 for further details

Raised planter: 3mm Cor-Ten steel 2500(h)x950(w)x950(h) as supplied by KITA (or similar approved)

Cycle stands: galvanised steel 'Sheffield' stands (700-1000mm in length and 750 high), 8no. at each location, as supplied by Broxap (or similar approved)

Litter bin: to match the existing type currently deployed by City of Edinburgh Council within the boundaries of the site

Bench: refer to bench schedule on sheet 1 for further details

Pedestrian wayfinding

ACD Multidrain channel - Please refer to drainage drawings for further details

Kerbs - Please refer to engineers drawings for further details

C01	20/03/20	DD+ UPDATES BASED ON UPDATED ENGINEERING INFO, DRAIN COMMENTS & ISSUE FOR CONSTRUCTION	SDR	ER	ER
P03	20/03/20	DD+ UPDATES BASED ON UPDATED ENGINEERING INFORMATION AND DRAIN COMMENTS	SDR	ER	ER
P02	20/03/20	DD+ UPDATES BASED ON DRAIN AND WORKSHOP COMMENTS AND UPDATED SCHEME ELEMENTS	SDR	ER	ER

Rev.	Date	Description	Drawn	Chkd.	Appd.

SENER FAIRHURST

Project Title:

EDINBURGH TRAM
YORK PLACE TO NEWHAVEN

Drawing Title:

LANDSCAPE PROPOSALS
DETAILED DESIGN
SHEET 3 OF 15

Scale at A1:	1:500	Status:	FOR CONSTRUCTION
Drawn:	SDR	Checked:	LF
		Approved:	ER
Date:	20/03/20	Date:	01/05/20
		Date:	01/05/20
Project:	Originator:	Volume:	Location:
		Type:	Rule:
		Number:	
ETYN-SEF-XXX-XX-DR-L-0018			
Submittal:	A1		Revision:
			C01